

Grease nozzles LAGS 8

The SKF LAGS 8 Grease nozzle kit provides the user with practical accessories for daily lubrication such as connectors, couplings and nozzles most widely used in the industry.

Grease nipples LAGN 120

To meet all of your needs for grease lubrication points, SKF has developed a grease fitting kit, LAGN 120, which contains a full range of 120 standardised conical grease fittings made of precision steel, zinc plated, hardened and blue chromated.



Contents LAGS 8

Straight pipe 180 mm and nozzle
Hose
Tube
Tube with nose piece and plastic transparent cover
Nipple M10x1-G1/8
Nipple M10x1-1/8-27NPS
Nozzle (2x)

Technical data

Designation	LAGS 8
Maximum working pressure	40 MPa (5,800 psi)
Minimum bursting pressure	80 MPa (11,600 psi)

Contents LAGN 120

Grease nipple		Quantity
M6x1	straight	30x
M8x1	straight	20x
M10x1	straight	10x
G 1/8	straight	10x
M6x1	45°	5x
M8x1	45°	10x
M10x1	45°	5x
G1/8	45°	5x
M6x1	90°	5x
M8x1	90°	10x
M10x1	90°	5x
G1/8	90°	5x

Technical data

Designation	LAGN 120
Maximum working pressure	40 MPa (5,800 psi)
Minimum burst pressure	80 MPa (11,600 psi)
Standard	DIN 71412
Material	Hardened

